AddOn Computer
34A Mauchly
Irvine, Ca 92618

Office: 949.861.2800
Fax: 949.861.2812
www.addoncomputer.com

MEDIA CONVERTERS - MEMORY UPGRADES
BATTERIES - NETWORKING TRANSCEIVERS

10/100/1000M TX-XX

1000BASE-TX To 1000BASE-FX
Gigabit Ethernet Media Converter

Features

Interface/Ports:	1 x RJ-45, 1 X SC or ST
Connectivity:	Twisted Pair, Fiber
Connectivity Media:	10/100/1000Base-T Twisted Pair 1000Base-XX (50/125 μm, 62.5/125 μm MMF) (9/125 μm SMF)
Distance Supported:	550m, 2km, 20km
Wavelength:	850nm, 1310nm, 1550nm
Network Technology:	10/100/1000Base-T 1000Base-XX(SX,LX,BX)
Status Indicators:	Power Copper Link Fiber Link Copper Receive activity Fiber Receive activity
Input Voltage:	5V AC/DC
Input Current:	500mA
Temperature:	32°F (0°C) ~ 122°F (50°C)
Humidity:	5 ~ 90% Non-condensing

Product Description

AddOn Media Converters and Network Interface Cards are 100% compliant for all of our networking needs. The 10/100/1000M TX-XX media converters provides a cost effective conversion from 1000Base Copper to 1000Base-XX fiber, while extending your network reach beyond the 100m reach limitation of copper. Economically priced.

ADD-GMC-SX-5SC
Media Converter 1000BTX-1000BSX
10/100/1000B-T 850NM MMF SC 550m

ADD-GMC-LX-2SC
Media Converter 1000BTX-1000BLX
10/100/1000B-T 1310NM SMF SC 20km

ADD-GMC-BX-USC
Media Converter 1000BTX-1000BXU
1310/1550NM BiDi SMF SC 20km Reach

ADD-GMC-BX-DSC
Media Converter 1000BTX-1000BXD
1550/1310NM BiDi SMF SC 20km Reach

ADD-GMC-SFP*
Media Converter 1000BTX-SFP
10/100/1000M with open SFP slot

ADD-GMC-SX-5ST
Media Converter 1000BTX-1000BSX
10/100/1000B-T 850NM MMF ST 550m

ADD-GMC-LX-2ST
Media Converter 1000BTX-1000BLX
10/100/1000B-T 1310NM SMF ST 20km

ADD-GMC-BX-UST
Media Converter 1000BTX-1000BXU
1310/1550NM BiDi SMF ST 20km Reach

ADD-GMC-BX-DST
Media Converter 1000BTX-1000BXD
1550/1310NM BiDi SMF ST 20km Reach

ADD-GMC-SX-2SC
Media Converter 1000BTX-1000BSX
10/100/1000B-T 1310NM MMF SC 2km

*For complete list of SFP/SFP module
please visit www.addoncomputer.com